

50DW-SFP10G-50.12-C

Cisco® 50DW-SFP10G-50.12 Compatible TAA 10GBase-DWDM SFP+ Transceiver C-Band Channel DW34 100GHz (SMF, 1550.12nm, 80km, LC, DOM)

Features:

- SFF-8432 and SFF-8472 Compliance
- Duplex LC Connector
- Single-mode Fiber
- Commercial Temperature 0 to 70 Celsius
- Hot Pluggable
- Metal with Lower EMI
- Excellent ESD Protection
- RoHS Compliant and Lead Free



Applications:

- 10x Gigabit Ethernet over DWDM
- 8x/10x Fibre Channel
- Access, Metro and Enterprise

Product Description

This Cisco® 50DW-SFP10G-50.12 compatible SFP+ transceiver provides 10GBase-DWDM throughput up to 80km over single-mode fiber (SMF) using a wavelength of 1550.12nm via an LC connector. It is guaranteed to be 100% compatible with the equivalent Cisco® transceiver. This easy to install, hot swappable transceiver has been programmed, uniquely serialized and data-traffic and application tested to ensure that it will initialize and perform identically. Digital optical monitoring (DOM) support is also present to allow access to real-time operating parameters. This transceiver is Trade Agreements Act (TAA) compliant. We stand behind the quality of our products and proudly offer a limited lifetime warranty.

ProLabs's transceivers are RoHS compliant and lead-free.

TAA refers to the Trade Agreements Act (19 U.S.C. & 2501-2581), which is intended to foster fair and open international trade. TAA requires that the U.S. Government may acquire only "U.S. – made or designated country end products."



Wavelength Guide

| Channel # | Center Wavelength (nm) | Channel # | Center Wavelength (nm) |
|-----------|------------------------|-----------|------------------------|
| 18 | 1563.05 | 40 | 1545.32 |
| 19 | 1562.23 | 41 | 1544.53 |
| 20 | 1561.42 | 42 | 1543.73 |
| 21 | 1560.61 | 43 | 1542.94 |
| 22 | 1559.79 | 44 | 1542.14 |
| 23 | 1558.98 | 45 | 1541.35 |
| 24 | 1558.17 | 46 | 1540.56 |
| 25 | 1557.36 | 47 | 1539.77 |
| 26 | 1556.55 | 48 | 1538.98 |
| 27 | 1555.75 | 49 | 1538.19 |
| 28 | 1554.94 | 50 | 1537.40 |
| 29 | 1554.13 | 51 | 1536.61 |
| 30 | 1553.33 | 52 | 1535.82 |
| 31 | 1552.52 | 53 | 1535.04 |
| 32 | 1551.72 | 54 | 1534.25 |
| 33 | 1550.92 | 55 | 1533.47 |
| 34 | 1550.12 | 56 | 1532.68 |
| 35 | 1549.32 | 57 | 1531.90 |
| 36 | 1548.51 | 58 | 1531.12 |
| 37 | 1547.72 | 59 | 1530.33 |
| 38 | 1546.92 | 60 | 1529.55 |
| 39 | 1546.12 | 61 | 1528.77 |

Absolute Maximum Ratings

| Parameter | Symbol | Min. | Typ. | Max. | Unit | Notes |
|------------------------|--------|------|---------|-------------------|------|-------|
| Storage Temperature | Tstg | -40 | | 85 | °C | |
| Operating Temperature | Tc | 0 | | 70 | °C | |
| Supply Current | Icc | | 450 | 500 | mA | 1 |
| Data Rate | DR | 1.2 | 10.3125 | 11.3 | Gbps | 2 |
| Maximum Supply Voltage | Vcc | -0.5 | | 4.0 | V | 1 |
| Bit Error Rate | BER | | | 10 ⁻¹² | | |

Notes:

1. For electrical power interface.
2. IEEE 802.3ae.

Electrical Characteristics

| Parameter | Symbol | Min. | Typ. | Max. | Unit | Notes |
|-------------------------------------|---------|------|------|----------|------|-------|
| Power Supply Voltage | Vcc | 3.14 | 3.3 | 3.46 | V | |
| Transmitter | | | | | | |
| Input Differential Impedance | RIN | | 100 | | | |
| Differential Data Input Swing | VIN,pp | 300 | | 850 | mV | |
| Transmit Disable Voltage | VD | 2 | | Vcc | V | |
| Transmit Enable Voltage | VEN | Vee | | Vee+0.8 | V | |
| Receiver | | | | | | |
| Differential Data Output Swing | VOUT,pp | 300 | | 850 | mV | |
| Data Output Rise/Fall Time (20-80%) | Tr/Tf | 28 | | | ps | |
| LOS Fault | Vlosa | 2 | | Host_Vcc | V | |
| LOS Normal | Vlosd | Vee | | Vee+0.5 | V | |

Optical Characteristics

| Parameter | Symbol | Min. | Typ. | Max. | Unit | Notes |
|---------------------------------|-----------------|------------------|-------------|------------------|-------|-------|
| Transmitter | | | | | | |
| Output Optical Power | Ptx | 0 | | 4 | dBm | 1 |
| Optical Center Wavelength | λ_C | $\lambda_C-0.05$ | λ_C | $\lambda_C+0.05$ | | 2 |
| Extinction Ratio | ER | 9 | | | dB | |
| Spectral Width (-20dB) | $\Delta\lambda$ | | | 0.6 | nm | |
| Side Mode Suppression Ratio | SMSR | 30 | | | dB | |
| Relative Intensity Noise | RIN | | | -128 | dB/Hz | |
| Transmitter Dispersion Penalty | TDP | | | 3.2 | dB | |
| Launch Power of Off Transmitter | Poff | | | -30 | dBm | 1 |
| Receiver | | | | | | |
| Optical Center Wavelength | λ_C | 1260 | | 1620 | nm | |
| Average Receive Power | Prx | -24 | | -7 | dBm | |
| Receiver Sensitivity @10.3Gbps | S | | | -24 | dBm | 3 |
| Receiver Reflectance | RR | | | -27 | dB | |
| LOS Assert | LOSA | -35 | | | dBm | |
| LOS De-Assert | LOSD | | | -27 | dBm | |
| LOS Hysteresis | LOSH | 0.5 | | | dB | |

Notes:

1. Average.
2. λ = specified ITU grid wavelength.
3. Measured with the PRBS 2³¹-1 test mode and BER<10⁻¹².

Pin Descriptions

| Pin | Symbol | Name/Description | Notes |
|-----|------------|--|-------|
| 1 | VeeT | Transmitter Ground. Common with Receiver Ground. | 1 |
| 2 | Tx_Fault | Transmitter Fault. | |
| 3 | Tx_Disable | Transmitter Disable. Laser output disables on “high” or “open.” | 2 |
| 4 | SDA | 2-Wire Serial ID Interface Data Line. | 3 |
| 5 | SCL | 2-Wire Serial ID Interface Clock Line. | 3 |
| 6 | MOD_ABS | Module Absent. Grounded within the module. | 3 |
| 7 | RS0 | Rate Select 0. Not used. | |
| 8 | LOS | Loss of Signal Indication. "Logic 0" indicates normal operation. | 4 |
| 9 | RS1 | Rate Select 1. Not used. | 1 |
| 10 | VeeR | Receiver Signal Ground. Common with Transmitter Ground. | 1 |
| 11 | VeeR | Receiver Signal Ground. Common with Transmitter Ground. | 1 |
| 12 | RD- | Inverse Received Data Out. AC Coupled. | |
| 13 | RD+ | Non-Inverted Receiver Data Out. AC Coupled. | |
| 14 | VeeR | Receiver Signal Ground. Common with Transmitter Ground. | 1 |
| 15 | VccR | Receiver Power Supply. | |
| 16 | VccT | Transmitter Power Supply. | |
| 17 | VeeT | Transmitter Signal Ground. Common with Receiver Ground. | 1 |
| 18 | TD+ | Transmitter Non-Inverted Data In. AC Coupled. | |
| 19 | TD- | Transmitter Inverted Data In. AC Coupled. | |
| 20 | VeeT | Transmitter Signal Ground. | 1 |

Notes:

1. Circuit ground is isolated from the chassis ground.
2. Disabled: Tdis>2V or open. Enabled: Tdis<0.8V.
3. Should be pulled up with 4.7kΩ to 10kΩ on the host board to a voltage between 2V and 3.46V.
4. LOS is open collector output.

Block Diagram of Transceiver



Electrical Pad Layout



Top of Board



Bottom of Board



Mechanical Specifications



About ProLabs

Our experience comes as standard; for over 15 years ProLabs has delivered optical connectivity solutions that give our customers freedom and choice through our ability to provide seamless interoperability. At the heart of our company is the ability to provide state-of-the-art optical transport and connectivity solutions that are compatible with over 90 optical switching and transport platforms.

Complete Portfolio of Network Solutions

ProLabs is focused on innovations in optical transport and connectivity. The combination of our knowledge of optics and networking equipment enables ProLabs to be your single source for optical transport and connectivity solutions from 100Mb to 400G while providing innovative solutions that increase network efficiency. We provide the optical connectivity expertise that is compatible with and enhances your switching and transport equipment.

Trusted Partner

Customer service is our number one value. ProLabs has invested in people, labs and manufacturing capacity to ensure that you get immediate answers to your questions and compatible product when needed. With Engineering and Manufacturing offices in the U.K. and U.S. augmented by field offices throughout the U.S., U.K. and Asia, ProLabs is able to be our customers best advocate 24 hours a day.



Contact Information

ProLabs US

Email: sales@prolabs.com

Telephone: 952-852-0252

ProLabs UK

Email: salesupport@prolabs.com

Telephone: +44 1285 719 600